

epcom[®]

Professional Video Surveillance Solutions

TURBO HD DVR

8-CH 4K/8MP 1U H.265 AcuSense

EX-8008-TURBO



KEY FEATURE

- 8 channels and 1 HDD 1U AcuSense DVR
- Support 4-ch Facial Recognition or 8-ch advanced model Perimeter Protection based on Deep Learning algorithm
- Efficient H.265 pro+ compression technology
- Encoding ability up to 4K @ 8fps; 3K/5MP @12fps
- Up to 16 channels IP camera inputs, each channel up to 8MP
- Up to 24*1080P@30fps decoding ability
- 5 signals input adaptively (HDTVI/AHD/CVI/CVBS/IP)
- Support All channels Motion Detection technology

COMPRESSION AND RECORDING

- H.265 Pro+ can be enabled to improve encoding efficiency and reduce data storage costs
- Recording at up to 8 MP resolution

NETWORK & ETHERNET ACCESS

- Support Hik-Connect & DDNS (Dynamic Domain Name System)
- Output bandwidth limit configurable

SMART FUNCTION


- Up to 8 channels (analog channel) Motion Detection 2.0
- Up to 8 channels (advanced model model, analog channel) Perimeter Protection
- Up to 4 channels (advanced model model, analog channel) human face recognition
- Support smart playback to enhance playback efficiency

SPECIFICATION


Specification	Description
Facial Recognition	
Face Picture Library	Up to 16 face picture libraries; HDD damage will not cause data loss in the face picture library, because the library has been backed up by HDD and flash.
Face Picture Comparison	4 ch face picture comparison alarm (HD analog camera)
Perimeter Protection	
Human/Vehicle Analysis	Up to 8 ch (advanced model)
Facial Detection and Capture	Face picture detection, face picture search; 4 ch face picture capture
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	8 MP/5 MP/3K/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF
Frame Rate	Main stream: 8 MP@8 fps/3K@12 fps/5 MP@12 fps/4 MP@15 fps/8 MP Lite@15 fps/3 MP@18 fps; 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N)
Sub stream:	WD1/4CIF/CIF@25 fps (P)/30 fps (N)
Video Bitrate	32 Kbps to 10 Mbps
Dual Stream Support	Yes
Stream Type	Video, Video & Audio
Audio	
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	
IP Video Input	8 ch (up to 16 ch), each up to 4 Mbps; Support H.265+/H.265/H.264+/H.264 IP cameras
Analog Video Input	8 ch; BNC interface (1.0 Vp p, 75 Ω), supporting coaxitron connection
HDMI Output	1 ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz; HDMI/VGA simultaneous output
VGA Output	1 ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz; HDMI/VGA simultaneous output
CVBS Input	PAL/NTSC
CVBS Output	1 ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
Synchronous Playback	8 ch
HDTV Input	8 MP(3840 × 2160)@15 fps, 8 MP(3840 × 2160)@12 fps, 3K(2960 × 1665)@20 fps, 5 MP(2560 × 1944)@20 fps, 5 MP(2560 × 1944)@12 fps, 4 MP(2560 × 1440)@30 fps, etc.
AHD Input	5 MP(2560 × 1944)@20 fps, 5 MP(2560 × 1944)@12 fps, 4 MP(2560 × 1440)@30 fps, 4 MP(2560 × 1440)@25 fps, 1080p@30 fps, 720p@30 fps, etc.
HDCVI Input	8 MP(3840 × 2160)@15 fps, 8 MP(3840 × 2160)@12 fps, 5M(2880 × 1620)@25 fps, 5 MP(2592 × 1944)@20 fps, 4 MP(2560 × 1440)@30 fps, 720p@30 fps, etc.
Audio Output	1 ch, RCA (Linear, 1 KΩ)
Audio Input	1 ch, RCA (2.0 Vp-p, 1 KΩ), 8 ch via coaxial cable
Two-Way Audio	1 ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audio input)

Specification	Description
Decoding	
Decoding Capability	up to 24 ch 1080P@30fps
Network	
Total Bandwidth	256 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, ISUP
Remote Connection	64
Network Interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	up to 12 TB capacity for each disk
Serial Interface	RS-485 (half-duplex)
USB Interface	Front panel: 1 × USB 2.0; Rear panel: 2 × USB 3.0
Alarm In/Out	N/A (optional to support)
General	
Power Supply	12 VDC, 2 A
Consumption	≤ 24 W
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	320 × 240 × 48 mm (12.6 × 9.4 × 1.9 inch)
Weight	≤ 2 kg (4.4 lb)

DIMENSION



PHYSICAL INTERFACE



Specification	Description	No.	Description
1	Video in	6	LAN network interface and USB interface
2	Audio out	7	12 VDC power input
3	HDMI interface	8	GND
4	VGA interface	9	Audio in
5	RS-485 interface	10	Video out