



# GDS3710

## HD IP Video Door System

The GDS3710 is an IP Video Door System that also serves as a high-definition IP surveillance camera and IP intercom to offer facility access control and security monitoring for buildings of all sizes. This powerful IP Video Door System offers a 180 degree video viewing angle for wall-to-wall coverage, has a built-in RFID chip reader for secure keyless entry, includes a built-in microphone and speaker to support intercom functionality and offers alarm-in and alarm-out support for integration with existing security devices. The GDS3710 integrates with a fully-managable utility software, GDS management software, allowing RFID card information to be loaded directly to the software as well as video feed management. Powered by an advanced Image Sensor Processor (ISP) and state-of-the-art image algorithms, the GDS3710 delivers 1080p FHD video resolutions and offers exceptional performance in all lighting conditions. It features SIP/VoIP technology with 2-way audio and video streaming feeds loaded directly to smart phones, SIP endpoints and the GDS management software. The GDS3710 is equipped with integrated PoE for seamless installation, bright LEDs for illumination, motion detector for security protection, lighting control switch and more. For surveillance use, the combination of the GDS3710 video system, mobile applications and Grandstream's GVR350x NVR provide a powerful recording and monitoring solution.



Powerful video resolutions up to 1080p



Built-in RFID chip reader for keyless entry (2 RFID cards included)



SIP/VoIP support allows for streaming of video feeds to multiple smartphones, SIP endpoints & software simultaneously



Built with a metal casing to make it weatherproof and vandal resistant



Built-in hemispheric camera allows for 180 degree wall-to-wall coverage



Supports motion detection



Integrated PoE to power the device and provide a network connection



Built-in microphone and speaker offers voice options and intercom functionality

|                                 |   |
|---------------------------------|---|
| <b>Video Compression</b>        | H.264 High Profile / Main Profile / Base Profile, Motion JPEG   |
| <b>Image Sensor Resolution</b>  | 1/2.7", 2 Megapixel, 1920H x 1080V  |
| <b>Lens Type</b>                | 1/2", F2.5, FOV: 180°(W) x 150°(H)  |
| <b>Day &amp; Night</b>          | White LEDs with smart brightness control  |
| <b>Max Video Resolution</b>     | 1920x1080   |
| <b>Max Frame Rate</b>           | 30 frames per second  |
| <b>Minimum Illumination</b>     | 0.5Lux  |
| <b>Wide Dynamic Range</b>       | Yes, up to 120db  |
| <b>Video Bit Rates</b>          | 32 Kbps to 8 Mbps, multi-rate for preview & recording   |
| <b>Embedded Analytics</b>       | Motion detection  |
| <b>Snapshots</b>                | Triggered upon events, sent via email and/or FTP  |
| <b>Multi-Stream Resolution</b>  | High-performance streaming server allowing multiple simultaneous access:<br><b>Primary video stream:</b> 1920 x 1080 resolution for continuous full HD recording<br><b>Secondary video stream:</b> 640 x 480 resolution for SIP/VoIP video calls<br><b>Third video stream:</b> 320 x 240 resolution for smartphone applications |
| <b>Network Protocol</b>         | TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS local upload and mass provisioning using TR-069 (pending), ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, SMTP, TFTP, NTP, STUN, SIMPLE, LLDP-MED, LDAP, 802.1x, TLS, SRTP  |
| <b>SIP/VoIP Support</b>         | Broad interoperability with most 3rd party SIP/VoIP devices and leading SIP/NGN/IMS platforms   |
| <b>Voice Codecs</b>             | G.711μ/a-law, G.722, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO), AEC  |
| <b>QoS</b>                      | Layer 2 QoS (802.1Q, 802.1P) and Layer 3 QoS (ToS, DiffServ, MPLS)  |
| <b>Security</b>                 | User and administrator level access control (pending), MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control   |
| <b>Upgrade/ Provisioning</b>    | Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using TR-069 (Pending) or AES encrypted XML configuration file  |
| <b>Audio Input</b>              | Built-in microphone, up to 1.5m with AEC  |
| <b>Audio Output</b>             | Built-in HD loudspeaker, sound quality suitable for up to 3 m   |
| <b>Button</b>                   | 12-key touchpad plus a capacitive doorbell button, each with individual LED illumination  |
| <b>RFID</b>                     | 125KHz: EM4100 (2 RFID cards included)  |
| <b>Alarm Input</b>              | Yes, 2 channels, Vin < 15V, for door sensor or other devices  |
| <b>Alarm Output</b>             | Yes, 2 channels, 125VAC/0.5A, 30VDC/2A, Normal Open or Normal Close, for electric lock, light switch or other devices   |
| <b>Network Interface</b>        | 10M/100M auto-sensing, RJ45   |
| <b>Expansion Interface</b>      | RS485, Wiegand input and output   |
| <b>Weight</b>                   | 0.6Kg   |
| <b>Dimensions (H x W x D)</b>   | 173mm(H) x 80mm(W) x 36mm(D)  |
| <b>Power Supply</b>             | PoE IEEE 802.3af Class 3, or 12VDC/1A connection (AC power adapter not included)  |
| <b>Ingress Protection</b>       | Weather proof, vandal resistant, with support for extra back reinforcing metal plate  |
| <b>Temperature and Humidity</b> | Operation: -30°C to 55°C (-22°F to 131°F)<br>Storage: -35°C to 60°C (-31°F to 140°F)<br>Humidity: 10% to 90% Non-condensing   |
| <b>Protection Class</b>         | IP65, IK06  |
| <b>Compliance</b>               | Part 15, Subpart B Class B; Part 15C, MPE; EN55022 Class B, EN61000-3-2, EN61000-3-3, EN50130, EN60950-1, EN 300328, EN300330, EN62479, EN 301489, EN302291, EN50364, EN60529; AS/NZS CISPR22 and AS/NZS4268, AS/NZS 60950  |